

# AccuRator D3

## Technical Datasheet

### General

**Dimensions:** 25" x 20" x 9"

**Weight:** 36 lbs

**Allowable Ambient Temperature:**  
40°-110°F (4°-43°C)

**Operating Environment:** Indoors

### Connections

**Water Inlet:** ¾" Hose Bib | ½" FNPT

**Ingredient Inlet (3x) and Return (3x):**  
Push-to-connect for ¼" OD Tubing

**Ingredient Outlet (3x):** ¼" Hose Barb

### Electrical

**Voltage:** 100-240V ; 50/60 hz

**Max Current:** 4.0 Amps @ 115 VAC

**Typical Current:** 1.5 Amps @ 115 VAC

**Tablet Bluetooth Range:** approx. 100 FT

### Operational Details

**Minimum Water Pressure:** 35 PSI

**Number of Ingredients:** up to 3

**Ingredient Flow Range:** up to 64 oz/min\*

**Accuracy:** +/- 5%

### Materials of Construction

**Case:** Glass Filled Polypropylene

**Wetted Materials:** Stainless Steel,  
Polypropylene, Polyurethane, Tritan, Acetal,  
FKM, Santoprene, HNBR

### NOTES:

- Ingredient containers should not be placed more than 4 ft below the AccuRator.
- Outlet hoses should be positioned at the same height or below the AccuRator.
- Inquire for material compatibility.
- \* Flow rate based on water. Alternative orifices available for higher flow ranges.



Contact CFVI Technical Support  
TechSupport@CFVI.com  
+1 (949) 414-9914  
for clarifications or inquiries