

AccuRator M3

Technical Datasheet

General

Dimensions: 25" x 20" x 9"

Weight: 38 lbs

Allowable Ambient Temperature:
40°-110°F (4°-43°C)

Operating Environment: Indoors

Connections

Water Inlet: ¾" Hose Bib | ½" FNPT

Ingredient Inlet (3x) and Return (3x):
Push-to-connect for ¼" OD Tubing

Product Outlet: ½" Hose Barb

Electrical

Voltage: 100-240V ; 50/60 hz

Max Current: 4.0 Amps @ 115 VAC

Typical Current: 1.5 Amps @ 115 VAC

Tablet Bluetooth Range: approx. 100 FT

Operational Details

Minimum Water Pressure: 35 PSI

Number of Ingredients: up to 3

Mixer Output Flow Rate: 2 GPM

Ingredient Flow Range: up to 32 oz/min*

Accuracy: +/- 5%

Materials of Construction

Case: Glass Filled Polypropylene

Wetted Materials: Stainless Steel,
Polypropylene, Polyurethane, Tritan, Acetal,
Nylon, FKM, Santoprene, HNBR

NOTES:

- Ingredient containers should not be placed more than 4 ft below the AccuRator.
- Outlet hoses should be positioned at the same height or below the AccuRator.
- Inquire for material compatibility.
- * Flow rate based on water. Alternative orifices available for higher flow ranges.



Contact CFVI Technical Support
TechSupport@CFVI.com
+1 (949) 414-9914
for clarifications or inquiries